

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
T. 16 S., R. 63 E., MDM, NEVADA

CHAINS

From this same corner, the $\frac{1}{4}$ sec. cor. of secs. 25 and 30, monumented with an iron post, 1 in. diam., firmly set showing 8 ins. above the ground, with brass cap mkd. as described in the field notes of the independent resurvey of the E. bdy. of T. 16 S., R. 63 E., executed under Group No. 317, bears N. $89^{\circ} 59'$ E., 16.56 chs. dist. Hereafter, this corner will function as an amended monument.

Add the marks "AM 1987" to the brass cap.

From the $\frac{1}{4}$ sec. cor. of secs. 13 and 24, monumented with an iron post, 1 in. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the survey of the subdivisional lines, T. 16 S., R. 63 E., executed under Group No. 317. Remark the brass cap to read as follows:

T16S R63E

S 13

$\frac{1}{4}$ S 24

1941

1987

EAST, bet. secs. 13 and 24.

Over mountainous land, covered with scattered chaparral, creosote and cacti.

23.09

Intersect the W. bdy. of sec. 18, T. 16 S., R. 64 E.

Point for the closing cor. of secs. 13 and 24.

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T16S

R63E R64E

S 13

CCS 24 S 18

1987

Set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the stainless steel post.

From this corner, the cor. of secs. 18 and 19, T. 16 S., R. 64 E., monumented with a stainless steel post, $2\frac{1}{2}$ ins. diam., firmly set showing 4 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the W. bdy. of T. 16 S., R. 64 E., executed concurrently under this same Group, bears S. $0^{\circ} 12'$ E., 5.34 chs. dist.

From this same corner, the cor. of secs. 13, 18, 19 and 24, monumented with an iron post, 2 ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the independent resurvey of the E. bdy. of T. 16 S., R. 63 E., executed under Group No. 317, bears EAST, 16.93 chs. dist. Hereafter, this corner will function as an amended monument.

Add the marks "AM 1987" to the brass cap.