## DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 16 S., R. 63 E., MDM, NEVADA

CHAINS

From this same corner, the true point for the  $\frac{1}{4}$  sec. cor. of secs. 7 and 12, as described in the field notes of the independent resurvey of the E. bdy. of T. 16 S., R. 63 E., executed under Group No. 317, bears N. 89° 56' E., 17.27 chs. dist.

## From which

The witness cor. for the \$\frac{1}{4}\$ sec. cor. of secs. 7 and 12, monumented with an iron post, 1 in. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the independent resurvey of the E. bdy. of T. 16 S., R. 63 E., executed under Group No. 317, bears NORTH, 0.57 chs. dist. Hereafter, this corner will function as an amended monument.

Add the marks "AM 1987" to the brass cap.

Point for the true point for the E  $\frac{1}{4}$  sec. cor. of sec. 1 at the intersection with the W. bdy. of sec. 6, T. 16 S., R. 64 E., and the E. and W. centerline of sec. 1.

From this point, point selected for the witness corner for the E  $\frac{1}{2}$  sec. cor. of sec. 1, bears N. 0° 12' W., 6.06 chs. dist.

Set a stainless steel post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins. in the ground to solid rock and in a mound of stone, 5 ft. base to top, with brass cap mkd.



From this point, the true point for the  $\frac{1}{4}$  sec. cor. of sec. 6, T. 16 S., R. 64 E., as described in the field notes of the dependent resurvey of the W. bdy. of T. 16 S., R. 64 E., executed concurrently under this same Group, bears S. 0° 12' E., 5.39 chs. dist.

## From which

The witness cor. for the  $\frac{1}{4}$  sec. cor. of sec. 6, T. 16 S., R. 64 E., monumented with a stainless steel post,  $2\frac{1}{2}$  ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the dependent resurvey of the W. bdy. of T. 16 S., R. 64 E., executed concurrently under this same Group, bears N. 2° 52' E., 4.05 chs. dist.

From this same point, the \( \frac{1}{4} \) sec. cor. of secs. 1 and 2, monumented with an iron post, 1 in. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the survey of the subdivisional lines of T. 16 S., R. 63 E., executed under Group No. 317, bears S. 89° 59' W. Remark the brass cap to read as follows: