TOWNSHIP 16 SOUTH, RANGE 64 EAST, MDM, NEVADA

 Reestablishment of the Survey Executed by R. H. Woods and W. H. Myrick, U.S. Deputy Surveyors, in 1881. The standard cor. of Tps. 16 S., Rs. 64 and 65 E., monumented with an aluminum post, 2½ ins. diam., firm set in a mound of stone, with aluminum cap mkd. as described in the field notes of the dependent resurve of the Fourth Standard Parallel South, through Range East, executed under Group No. 638. WEST, along the S. bdy. of sec. 36. Over nearly level land, covered with scattered chaparral, creosote and cacti. 12.14 The N ½ sec. cor. of sec. 7, T. 17 S., R. 65 E., monumented with a stainless steel post, 2½ ins. diam. firmly set in a mound of stone, with brass cap mkd. a described in the field notes of the dependent resurve of a portion of the west boundary of T. 17 S., R. 65 E., executed concurrently under this same Group. 40.00 Point for the standard ½ sec. cor. of sec. 36, at proportionate distance; there is no remaining evidenc of the original corner. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. Set a wooden post, 3 ins. square, 4 ft. long, alongsi the stainless steel post. 49.77 The closing cor. of Tps. 17 S., Rs. 64 and 65 E., monumented with a stainless steel post, 2½ ins. diam. firmly set showing 4 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the west boundary, T. 17 S., R. 65 E., executed concurrently under this same Group 51.50 Wash, 30 lks. wide, 2 ft. deep, drains NE. 79.82 Intersect Interstate Highway No. 15 right-of-way, bee S. 57 '56' W. and N. 57 '56' E. 	 R. H. Woods and W. H. Myrick, in 1881. The standard cor. of Tps. 16 S. monumented with an aluminum posset in a mound of stone, with a described in the field notes of of the Fourth Standard Parallel East, executed under Group No. WEST, along the S. bdy. of sec. Over nearly level land, covered chaparral, creosote and cacti. 12.14 The N ½ sec. cor. of sec. 7, T. monumented with a stainless stefirmly set in a mound of stone, described in the field notes of of a portion of the west bounda E., executed concurrently under 40.00 Point for the standard ½ sec. of proportionate distance; there i of the original corner. Set a stainless steel post, 28 diam., 24 ins. in the ground, w 	<pre>U.S. Deputy Surveyors, , Rs. 64 and 65 E., t, 2½ ins. diam., firm luminum cap mkd. as the dependent resurve South, through Range 638. 36. with scattered 17 S., R. 65 E., el post, 2½ ins. diam. with brass cap mkd. a the dependent resurve ry of T. 17 S., R. 65 this same Group. or. of sec. 36, at s no remaining evidence</pre>
 monumented with an aluminum post, 2½ ins. diam., firm set in a mound of stone, with aluminum cap mkd. as described in the field notes of the dependent resurve of the Fourth Standard Parallel South, through Range East, executed under Group No. 638. WEST, along the S. bdy. of sec. 36. Over nearly level land, covered with scattered chaparral, creosote and cacti. 12.14 The N ½ sec. cor. of sec. 7, T. 17 S., R. 65 E., monumented with a stainless steel post, 2½ ins. diam.firmly set in a mound of stone, with brass cap mkd. a described in the field notes of the dependent resurve of a portion of the west boundary of T. 17 S., R. 65 E., executed concurrently under this same Group. 40.00 Point for the standard ½ sec. cor. of sec. 36, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. Set a wooden post, 3 ins. square, 4 ft. long, alongsi the stainless steel post. 49.77 The closing cor. of Tps. 17 S., Rs. 64 and 65 E., monumented with a stainless steel post, 2½ ins. diam.firmly set showing 4 ins. above ground, with brass com kd. as described in the field notes of the dependent resurvey of a portion of the west boundary, T. 17 S., R. 65 E., executed concurrently under this same Group. 	 monumented with an aluminum posset in a mound of stone, with a described in the field notes of of the Fourth Standard Parallel East, executed under Group No. WEST, along the S. bdy. of sec. Over nearly level land, covered chaparral, creosote and cacti. 12.14 The N ½ sec. cor. of sec. 7, T. monumented with a stainless stefirmly set in a mound of stone, described in the field notes of of a portion of the west bounda E., executed concurrently under 40.00 Point for the standard ½ sec. cor proportionate distance; there i of the original corner. Set a stainless steel post, 28 diam., 24 ins. in the ground, w 	<pre>t, 2½ ins. diam., firm luminum cap mkd. as the dependent resurve South, through Range 638. 36. with scattered 17 S., R. 65 E., el post, 2½ ins. diam. with brass cap mkd. a the dependent resurve ry of T. 17 S., R. 65 this same Group. or. of sec. 36, at s no remaining evidence</pre>
 Over nearly level land, covered with scattered chaparral, creosote and cacti. 12.14 The N ½ sec. cor. of sec. 7, T. 17 S., R. 65 E., monumented with a stainless steel post, 2½ ins. diam. firmly set in a mound of stone, with brass cap mkd. a described in the field notes of the dependent resurve of a portion of the west boundary of T. 17 S., R. 65 E., executed concurrently under this same Group. 40.00 Point for the standard ½ sec. cor. of sec. 36, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. Set a wooden post, 3 ins. square, 4 ft. long, alongsit the stainless steel post. 49.77 The closing cor. of Tps. 17 S., Rs. 64 and 65 E., monumented with a stainless steel post, 2½ ins. diam. firmly set showing 4 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the west boundary, 7. 17 S., R. 65 E., executed concurrently under this same Group. 49.78 Wash, 30 lks. wide, 2 ft. deep, drains NE. 79.82 Intersect Interstate Highway No. 15 right-of-way, beat 	 Over nearly level land, covered chaparral, creosote and cacti. 12.14 The N ½ sec. cor. of sec. 7, T. monumented with a stainless stefirmly set in a mound of stone, described in the field notes of of a portion of the west boundare., executed concurrently under 40.00 Point for the standard ½ sec. coproportionate distance; there is of the original corner. Set a stainless steel post, 28 diam., 24 ins. in the ground, we see the standard ½ see the standare ½ see the standare ½ see the standare steel post, 28 diam., 24 ins. in the ground, we see the standare steel post, 28 diam. 	with scattered 17 S., R. 65 E., el post, 2½ ins. diam. with brass cap mkd. as the dependent resurvey ry of T. 17 S., R. 65 this same Group. or. of sec. 36, at s no remaining evidence
 chaparral, creosote and cacti. 12.14 The N ½ sec. cor. of sec. 7, T. 17 S., R. 65 E., monumented with a stainless steel post, 2½ ins. diam. firmly set in a mound of stone, with brass cap mkd. a described in the field notes of the dependent resurve of a portion of the west boundary of T. 17 S., R. 65 E., executed concurrently under this same Group. 40.00 Point for the standard ½ sec. cor. of sec. 36, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. Set a wooden post, 3 ins. square, 4 ft. long, alongsi the stainless steel post. 49.77 The closing cor. of Tps. 17 S., Rs. 64 and 65 E., monumented with a stainless steel post, 2½ ins. diam. firmly set showing 4 ins. above ground, with brass camkd. as described in the field notes of the dependent resurvey of a portion of the west boundary, T. 17 S., R. 65 E., executed concurrently under this same Group 51.50 Wash, 30 lks. wide, 2 ft. deep, drains NE. 79.82 Intersect Interstate Highway No. 15 right-of-way, beat 	 chaparral, creosote and cacti. 12.14 The N ½ sec. cor. of sec. 7, T. monumented with a stainless stefirmly set in a mound of stone, described in the field notes of of a portion of the west boundare., executed concurrently under 40.00 Point for the standard ½ sec. correspondent distance; there is of the original corner. Set a stainless steel post, 28 diam., 24 ins. in the ground, where the standard ½ sec. Sc Tl6S Ref ½ S 36 	17 S., R. 65 E., el post, 2½ ins. diam. with brass cap mkd. as the dependent resurvey ry of T. 17 S., R. 65 this same Group. or. of sec. 36, at s no remaining evidence
 monumented with a stainless steel post, 2½ ins. diam. firmly set in a mound of stone, with brass cap mkd. a described in the field notes of the dependent resurve of a portion of the west boundary of T. 17 S., R. 65 E., executed concurrently under this same Group. 40.00 Point for the standard ½ sec. cor. of sec. 36, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. Set a wooden post, 3 ins. square, 4 ft. long, alongsi the stainless steel post. 49.77 The closing cor. of Tps. 17 S., Rs. 64 and 65 E., monumented with a stainless steel post, 2½ ins. diam. firmly set showing 4 ins. above ground, with brass camkd. as described in the field notes of the dependent resurvey of a portion of the west boundary, T. 17 S., R. 65 E., executed concurrently under this same Group 51.50 Wash, 30 1ks. wide, 2 ft. deep, drains NE. 79.82 Intersect Interstate Highway No. 15 right-of-way, beat 	 monumented with a stainless ster firmly set in a mound of stone, described in the field notes of of a portion of the west boundare., executed concurrently under 40.00 Point for the standard 1/4 sec. of proportionate distance; there is of the original corner. Set a stainless steel post, 28 diam., 24 ins. in the ground, we stand the ground of the standard 1/4 Standare the standare	el post, 2½ ins. diam. with brass cap mkd. as the dependent resurvey ry of T. 17 S., R. 65 this same Group. or. of sec. 36, at s no remaining evidence
 proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. Sc T16S R64E ½ S 36 1987 Set a wooden post, 3 ins. square, 4 ft. long, alongsi the stainless steel post. 49.77 The closing cor. of Tps. 17 S., Rs. 64 and 65 E., monumented with a stainless steel post, 2½ ins. diam. firmly set showing 4 ins. above ground, with brass camkd. as described in the field notes of the dependent resurvey of a portion of the west boundary, T. 17 S., R. 65 E., executed concurrently under this same Group 51.50 Wash, 30 lks. wide, 2 ft. deep, drains NE. 79.82 Intersect Interstate Highway No. 15 right-of-way, beat 	proportionate distance; there i of the original corner. Set a stainless steel post, 28 diam., 24 ins. in the ground, w SC T16S R6 $\frac{1}{4}$ S 36	s no remaining evidence
 diam., 24 ins. in the ground, with brass cap mkd. SC T16S R64E <u>1/4</u> S 36 1987 Set a wooden post, 3 ins. square, 4 ft. long, alongsi the stainless steel post. 49.77 The closing cor. of Tps. 17 S., Rs. 64 and 65 E., monumented with a stainless steel post, 2½ ins. diam. firmly set showing 4 ins. above ground, with brass ca mkd. as described in the field notes of the dependent resurvey of a portion of the west boundary, T. 17 S., R. 65 E., executed concurrently under this same Group 51.50 Wash, 30 lks. wide, 2 ft. deep, drains NE. 79.82 Intersect Interstate Highway No. 15 right-of-way, beat 	diam., 24 ins. in the ground, w SC T16S R6 <u>達 S 36</u>	ins. long. 2½ ins.
 TI6S R64E <u>14</u> S 36 1987 Set a wooden post, 3 ins. square, 4 ft. long, alongsi the stainless steel post. 49.77 The closing cor. of Tps. 17 S., Rs. 64 and 65 E., monumented with a stainless steel post, 2½ ins. diam. firmly set showing 4 ins. above ground, with brass ca mkd. as described in the field notes of the dependent resurvey of a portion of the west boundary, T. 17 S., R. 65 E., executed concurrently under this same Group 51.50 Wash, 30 lks. wide, 2 ft. deep, drains NE. 79.82 Intersect Interstate Highway No. 15 right-of-way, beat 	T16S R6 날 S 36	ith brass cap mkd.
 ¹/₄ S 36 1987 Set a wooden post, 3 ins. square, 4 ft. long, alongsi the stainless steel post. 49.77 The closing cor. of Tps. 17 S., Rs. 64 and 65 E., monumented with a stainless steel post, 2¹/₂ ins. diam. firmly set showing 4 ins. above ground, with brass ca mkd. as described in the field notes of the dependent resurvey of a portion of the west boundary, T. 17 S., R. 65 E., executed concurrently under this same Group 51.50 Wash, 30 lks. wide, 2 ft. deep, drains NE. 79.82 Intersect Interstate Highway No. 15 right-of-way, beat 	1/4 S 36	4F
 Set a wooden post, 3 ins. square, 4 ft. long, alongsi the stainless steel post. 49.77 The closing cor. of Tps. 17 S., Rs. 64 and 65 E., monumented with a stainless steel post, 2½ ins. diam. firmly set showing 4 ins. above ground, with brass camkd. as described in the field notes of the dependent resurvey of a portion of the west boundary, T. 17 S., R. 65 E., executed concurrently under this same Group 51.50 Wash, 30 lks. wide, 2 ft. deep, drains NE. 79.82 Intersect Interstate Highway No. 15 right-of-way, beat 	1987	
 the stainless steel post. 49.77 The closing cor. of Tps. 17 S., Rs. 64 and 65 E., monumented with a stainless steel post, 2½ ins. diam. firmly set showing 4 ins. above ground, with brass camkd. as described in the field notes of the dependent resurvey of a portion of the west boundary, T. 17 S., R. 65 E., executed concurrently under this same Group 51.50 Wash, 30 lks. wide, 2 ft. deep, drains NE. 79.82 Intersect Interstate Highway No. 15 right-of-way, beat 		
 monumented with a stainless steel post, 2½ ins. diam. firmly set showing 4 ins. above ground, with brass camkd. as described in the field notes of the dependent resurvey of a portion of the west boundary, T. 17 S., R. 65 E., executed concurrently under this same Group 51.50 Wash, 30 lks. wide, 2 ft. deep, drains NE. 79.82 Intersect Interstate Highway No. 15 right-of-way, beam of the state of		e, 4 ft. long, alongsio
79.82 Intersect Interstate Highway No. 15 right-of-way, bea	monumented with a stainless ste firmly set showing 4 ins. above mkd. as described in the field resurvey of a portion of the we	el post, 2½ ins. diam. ground, with brass ca notes of the dependent st boundary, T. 17 S.,
	51.50 Wash, 30 1ks. wide, 2 ft. deep,	drains NE.
	79.82 Intersect Interstate Highway No S. 57°56'W. and N. 57°56'E.	. 15 right-of-way, beau