102

DEPENDENT RESURVEY OF THE FOURTH STANDARD PARALLEL SOUTH, THROUGH RANGE 64 EAST, MDM, NEVADA

_	SOUTH, THROUGH RANGE 64 EAST, MDM, NEVADA
chains 40.00	Point for the standard ¼ sec. cor. of sec. 31, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	SC T16S R64E ½ S 31
	1987
49.73	The closing cor. of secs. 7 and 8, T. 17 S., R. 64 E., monumented with a stainless steel post, 2½ ins. diam., firmly set showing 4 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 17 S., R. 64 E., executed concurrently under this same Group.
60.50	Wash, 30 lks. wide, 2 ft. deep, drains S.
72.00	Wash, 30 lks. wide, 2 ft. deep, drains S.
80.00	Point for the standard cor. of Tps. 16 S., Rs. 63 and 64 E., at record bearing and distance from the standard cor. of Tps. 16 S., Rs. 64 and 65 E.; there is no remaining evidence of the original corner. This corner will now refer to the SW cor. of T. 16 S., R. 64 E. only.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	SC T16S R64E <u>S</u> 31
	1987
	Set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the stainless steel post.
	DEPENDENT RESURVEY OF THE NORTH BOUNDARY, T. 16 S., R. 64 E., MOUNT DIABLO MERIDIAN, NEVADA
	Reestablishment of the Survey Executed by R. H. Woods, U.S. Deputy Surveyor, in 1881.
	From the cor. of Tps. 15 and 16 S., Rs. 64 and 65 E., monumented with an aluminum post, 2½ ins. diam., firmly set in a mound of stone, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 16 S., R. 65 E., executed under Group No. 638. N. 89° 43' W., along the N. bdy. of sec. 1.
	in. 05 To m., along the N. buy. of Sec. 1.