

DEPENDENT RESURVEY OF THE NORTH BOUNDARY,
T. 16 S., R. 64 E., MDM, NEVADA

CHAINS	
40.00	<p style="text-align: center;">T15S R64E <u>¼ S 32</u> T16S</p> <p style="text-align: center;">1987</p> <p>Point for the ¼ sec. cor. of secs. 5 and 32, at proportionate distance; there is no remaining evidence of the original corner. This corner will now refer to sec. 5 only.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone, 5 ft. base to top, with brass cap mkd.</p>
62.58	<p style="text-align: center;">T15S R64E <u>¼ S 5</u> T16S</p> <p style="text-align: center;">1987</p> <p>Point for the cor. of secs. 31 and 32, T. 15 S., R. 64 E., determined at 80 chs. in departure from the closing corner of the SW. cor. of T. 15 S., R. 64 E.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., on solid rock over a cross (X), in a mound of stone, 5 ft. base to top, with brass cap mkd.</p>
80.00	<p style="text-align: center;">T15S R64E <u>S 31 S 32</u> S 5 T16S</p> <p style="text-align: center;">1987</p> <p>Point for the cor. of secs. 5, 6, 31 and 32, at proportionate distance; there is no remaining evidence of the original corner. This corner will now refer to secs. 5 and 6 only.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p>
22.00	<p style="text-align: center;">T15S R64E S 31 <u>S 6 S 5</u> T16S</p> <p style="text-align: center;">1987</p> <hr/> <p>N. 89° 43' W., along the N. bdy. of sec. 6.</p> <p>Over rolling land, covered with scattered chaparral, creosote and cacti.</p>
22.58	<p>Enter mountainous land.</p> <p>Point for the S ¼ sec. cor. of sec. 31, T. 15 S., R. 64 E., determined at 40 chs. in departure from the closing corner of the SW. cor. of T. 15 16 S., R. 64 E.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>