

SURVEY OF PARCEL D, SECTIONS 17 AND 18,
T. 16 S., R. 64 E., MDM, NEVADA

	CHAINS	<p>Insert iron pipe inside stainless steel post and reset the wooden post alongside the stainless steel post.</p> <hr/> <p>N. 0° 06' W., on line 20-1, Parcel D.</p> <p>Over rolling land.</p> <p>9.93 Angle Point No. 1, Parcel D and point of beginning.</p> <hr/> <p style="text-align: center;">SURVEY FOR THE MINERAL SEGREGATION OF THE JORDAN MILLSITES 1 THROUGH 10, SECTIONS 17 AND 20, T. 16 S., R. 64 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>During the investigation and retracement of the millsites the location monumentation exceeded five acres as required under section 2337 of the Revised Statutes of the United States (30 U.S.C. 42), as amended by the Act of March 18, 1960, Public Law 86-390, 74 Stat. 7. These monuments are described in the field notes, however only the monuments used for control were remonumented.</p> <hr/> <p>Beginning at the NE. cor., Jordan Millsite No. 5, determined at distance from the SE cor., Jordan Millsite No. 5, as shown on Map NO. 834811 and on bearing extended from the SE cor., Jordan Millsite No. 6 through the SE cor., Jordan Millsite No. 5. This map in file 8, page 84, book 875, filed in Clark County on April 20, 1978.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T16S JM S 5 R64E COR NE S 17 MILLSITE </p> <p style="text-align: center;">1989</p> <p>S. 89° 56' W., on the N. bdy. of Jordan Millsites.</p> <p>Over rolling land.</p> <p>9.96 Point for the NW cor., Jordan Millsite No. 5, determined at distance from the SW cor., Jordan Millsite No. 5, as shown on map No. 834811 and on line 16-17 Parcel D.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p>	
--	--------	---	--