DEPENDENT RESURVEY OF A PORTION OF
DEFENDENT RESORTET OF A FORTION OF
THE SUBDIVISIONAL LINES,
T. 17 S., R. 64 E., MDM, NEVADA

T. 17 S., R. 64 E., MDM, NEVADA			
с	HAINS	T17S R64E S 12 ¼ S 13	
		1938 1987	
		From this same corner, the N ½ sec. cor. of sec. 12, monumented with an iron post, 1 in. diam., firmly set showing 6 ins. above ground, with brass cap mkd. as described in the field notes of the independent resurvey of the subdivisional lines of T. 17 S., R. 64 E., executed under Group 237, bears NORTH, 5.46 chs. dist. Hereafter, this cor. will function as an amended monument.	
		Add the marks "AM 1987" to the brass cap.	
		From which	
		The standard ½ sec. cor. of sec. 35, T. 16 S., R. 64 E., monumented with an iron post, 1 in. diam., firmly set showing 6 ins. above ground, with brass cap mkd. as described in the field notes of the independent resurvey of the Fourth Standard Parallel South, through Range 64 East, executed under Group No. 237, bears WEST, 14.155 chs. dist. Hereafter, this cor. will function as an amended monument.	
		Add the marks "AM 1987" to the brass cap.	
		From the $\frac{1}{4}$ sec. cor. of secs. 10 and 11, monumented with an iron post, 1 in. diam., firmly set showing 6 ins. above ground, with brass cap mkd. as described in the field notes of the independent resurvey of the subdivisional lines of T. 17 S., R. 64 E., executed under Group No. 237. Remark the brass cap to read as follows:	
		T175 R64E	
		S 10 S 11	
		1938 1987	
		NORTH, bet. secs. 10 and 11.	
		Over rolling land, covered with scattered chaparral, creosote and cacti.	
2	3.90	Intersect the Fourth Standard Parallel South.	
		Point for the closing cor. of secs. 10 and 11.	
		Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.	