

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES
T. 17 S., R. 64 E., MDM, NEVADA

CHAINS

From this corner, the standard cor. of secs. 34 and 35, T. 16 S., R. 64 E., monumented with a stainless steel post, 2½ ins. diam., firmly set showing 4 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the Fourth Standard Parallel South, through Range 64 East, executed concurrently under this same Group, bears EAST, 9.73 chs. dist.

From this same corner, the ¼ sec. cor. of secs. 11 and 14, monumented with an iron post, 1 in. diam., firmly set showing 6 ins. above ground, with brass cap mkd. as described in the field notes of the independent resurvey of the subdivisional lines of T. 17 S., R. 64 E., executed under Group No. 237, bears S. 0° 01' E. Remark the brass cap to read as follows:

T17S R64E
S 11
¼ S 14

1938
1987

From this same corner, the N ¼ sec. cor. of sec. 11, monumented with an iron post, 1 in. diam., firmly set showing 6 ins. above ground, with brass cap mkd. as described in the field notes of the independent resurvey of the subdivisional lines of T. 17 S., R. 64 E., executed under Group No. 237, bears N. 0° 01' W., 5.42 chs. dist. Hereafter, this cor. will function as an amended monument.

Add the marks "AM 1987" to the brass cap.

From which

The standard ¼ sec. cor. of sec. 34, T. 16 S., R. 64 E., monumented with an iron post, 1 in. diam., firmly set showing 6 ins. above ground, with brass cap mkd. as described in the field notes of the independent resurvey of the Fourth Standard Parallel South, through Range 64 East, executed under Group No. 237, bears WEST, 14.17 chs. dist. Hereafter, this cor. will function as an amended monument.

Add the marks "AM 1987" to the brass cap.

From the ¼ sec. cor. of sec. 9 and 10, monumented with an iron post, 1 in. diam., firmly set showing 6 ins. above ground, with brass cap mkd. as described in the field notes of the independent resurvey of the subdivisional lines of T. 17 S., R. 64 E., executed under Group No. 237. Remark the brass cap to read as follows:

T17S R64E
¼
S 9 | S 10

1938
1987

N. 0° 01' W., bet. secs. 9 and 10.