

182

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
T. 17 S., R. 64 E., MDM, NEVADA

<p>CHAINS</p> <p>23.86</p>	<p>Over gently rolling land, covered with scattered chaparral, creosote and cacti.</p> <p>Intersect the Fourth Standard Parallel South.</p> <p>Point for the closing cor. of secs. 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T16S R64E S 33 ----- S 91S 10 CC T17S R64E</p> <p style="text-align: center;">1987</p> <p>Set a wooden post, 4 ins. square, 4 ft. long, alongside the stainless steel post.</p> <p>From this corner, the standard ¼ sec. cor. of sec. 33, T. 16 S., R. 64 E., monumented with a stainless steel post, 2½ ins. diam., firmly set showing 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the Fourth Standard Parallel South, through Range 64 East, executed concurrently under this same Group, bears EAST, 9.63 chs. dist.</p> <p>From this same corner, the closing cor. of secs. 9 and 10, monumented with an iron post, 2 ins. diam., firmly set showing 6 ins. above ground, with brass cap mkd. as described in the field notes of the independent resurvey of the subdivisional lines of T. 17 S., R. 64 E., executed under Group No. 237, bears N. 0° 01 W., 5.40 chs. dist. Hereafter, this cor. will function as an amended monument.</p> <p>Add the marks "AM 1987" to the brass cap.</p> <p>From which</p> <p style="padding-left: 40px;">The standard cor. of secs. 32 and 33, T. 16 S., R. 64 E., monumented with an iron post, 2 ins. diam., firmly set showing 6 ins. above ground, with brass cap mkd. as described in the field notes of the independent resurvey of the Fourth Standard Parallel South, through Range 64 East, executed under Group No. 237, bears WEST, 14.22 chs. dist. Hereafter, this cor. will function as an amended monument.</p> <p style="padding-left: 40px;">Add the marks "AM 1987" to the brass cap.</p> <hr/> <p>Point for the N ¼ sec. cor. of sec. 10 at the intersection with the Fourth Standard Parallel South and the N - S center line of sec. 10.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
----------------------------	--