DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 17 S., R. 64 E., MDM, NEVADA

CHAINS

From the $\frac{1}{4}$ sec. cor. of secs. 7 and 8, monumented with an iron post, 1 in. diam., firmly set showing 6 ins. above ground, with brass cap mkd. as described in the field notes of the independent resurvey of the subdivisional lines of T. 17 S., R. 64 E., executed under Group No. 237. Remark the brass cap to read as follows:

T17S R64E S 7|S 8 1938 1987

N. 0° 03' W., bet. secs. 7 and 8.

Over nearly level land, covered with scattered chaparral, creosote and cacti.

23.64 Intersect the Fourth Standard Parallel South.

Point for the closing cor. of secs. 7 and 8.

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T16S R64E S 31 S 71S 8 CC T17S R64E

1987

Set a wooden post, 4 ins. square, 3 ft. long, alongside the stainless steel post.

From this corner, the standard $\frac{1}{4}$ sec. cor. of sec. 31, T. 16 S., R. 64 E., monumented with a stainless steel post, $2\frac{1}{2}$ ins. diam., firmly set showing 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the Fourth Standard Parallel South, through Range 64 East, executed concurrently under this same Group, bears EAST, 9.73 chs. dist.

From this same corner, the closing cor. of secs. 7 and 8, monumented with an iron post, 2 ins. diam., firmly set showing 6 ins. above ground, with brass cap mkd. as described in the field notes of the independent resurvey of the subdivisional lines of T. 17 S., R. 64 E., executed under Group No. 237, bears N. 0° 03' W., 5.34 chs. dist. Hereafter, this cor. will function as an amended monument.

Add the marks "AM 1987" to the brass cap.