

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 17 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY, T. 17 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA
	<p>Reestablishment of the Survey Executed by E. B. Monroe, U. S. Deputy Surveyor, in 1868 and the Resurvey Executed by R. W. Reilly and T. A. Magee, U. S. Deputy Surveyors, in 1881.</p> <hr/> <p>From the cor. of secs. 4, 5, 32 and 33, monumented with a basalt stone, 12X10X10 ins., firmly set, projecting 4 ins. above ground, mkd. 6 grooves on the S. face and 2 grooves on the W. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T17N R28E S 32 S 33 ----- S 5 S 4 T16N</p> </div> <p>1990</p> <p>Bury the original cornerstone and set a steel fence post, 5½ ft. long, alongside the stainless steel post.</p> <p>Cor. is located at the corner of fences, fences bear S. and W.</p> <p>N. 89°34' W., bet. secs. 5 and 32.</p> <p>Over rolling sandy hills, sagebrush.</p> <p>14.20 Ravine, drains N.</p> <p>28.90 Low sandy spur, slopes N.</p> <p>39.30 Trail road, bears NE. and SW.</p> <p>40.04 Point for the ¼ sec. cor. of secs. 5 and 32, determined by method of broken boundaries; there is no remaining evidence of the original cor.</p>