DEPENDENT RESURVEY OF THE WEST BOUNDARY, T. 17 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

	T. 17 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA
CHAINS	Bury the original cornerstone and set a steel fence post, 5½ ft. long, alongside the stainless steel post.
:	N. 0°28 E., along the W. bdy. of sec. 6.
	Over nearly level sandy terrain, hillocks with sparse sagebrush and native grass.
40.18	The ¼ sec. cor. of secs. 1 and 6, monumented with a basalt stone, 10X6X6 ins., firmly set, projecting 2 ins. above ground, mkd. ¼ on the W. face. This cor. will now refer to the ¼ sec. cor. of sec. 6 only.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T17N ¼ S 6 R28E
	1990
	Bury the original cornerstone and set a steel fence post, 5½ ft. long, alongside the stainless steel post.
	N. 0°21 E., beginning new measurement.
37.02	
37.02 40.10	Power line, bears S. 66° W. and N. 66° E.
	Power line, bears S. 66° W. and N. 66° E. The cor. of Tps. 17 and 18 N., Rs. 27 and 28 E., monumented with a basalt stone, 16X8X6 ins., firmly set, projecting 2 ins. above ground, mkd. with 6 notches on the NE., SE. and SW. edges and 6 grooves on
	Power line, bears S. 66° W. and N. 66° E. The cor. of Tps. 17 and 18 N., Rs. 27 and 28 E., monumented with a basalt stone, 16X8X6 ins., firmly set, projecting 2 ins. above ground, mkd. with 6 notches on the NE., SE. and SW. edges and 6 grooves on the W. face.