

TOWNSHIP 34 NORTH, RANGE 32 EAST, MDM, NEVADA

CHAINS

The rules of proportionate measurement were applied in order to ascertain the position of the lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and Special Instructions dated September 4, 1987 and Supplemental Special Instructions dated June 16, 1988.

The directions of the lines of this survey were determined by azimuth taken from U.S.C. & G.S. triangulation station "VABM 4488 (USGS)" located in section 15. The directions of the lines were carried forward throughout the township by sustained angulation.

The vertical angles of measurements made on the slope were ascertained with a theodolite in good adjustment; the horizontal equivalents only are entered in the field notes.

The geographic position of the southeast corner of the township is at latitude $40^{\circ} 45' 44.65''$ N. and longitude $118^{\circ} 18' 46.86''$ W., (NAD 27), as calculated from a direct tie to U.S.C. & G.S. triangulation station "VABM 4488 (USGS)".

The mean magnetic declination was found to be 16° E.

DEPENDENT RESURVEY OF THE WEST BOUNDARY,
T. 34 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
G.W. Garside and C.S. Preble, U.S. Deputy Surveyors,
in 1875.

The cor. of Tps. 33 and 34 N., Rs. 31 and 32 E., monumented with an iron post, 3 ins. diam., firmly set, exposed 12 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 34 N., R. 31 E., executed under Group No. 14. Add the marks 1988 to the brass cap.

N. $1^{\circ} 47'$ W., along the W. bdy. of sec. 31.