

SURVEY OF THE SUBDIVISIONAL LINES,
T. 34½ N., R. 32 E., MDM, NEVADA

CHAINS	
26.58	<p>From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., monumented with a stainless steel post, 2½ ins. diam., firmly set, exposed 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 34 N., R. 32 E., executed concurrently under this same Group.</p> <p>NORTH, bet. secs. 33 and 34.</p> <p>Over nearly level land, through scattered sagebrush and greasewood.</p> <p>Intersect the S. bdy. of sec. 34, T. 35 N., R. 32 E.</p> <p>Point for the closing cor. of secs. 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T35N R32E S 34 ----- S 33 S 34 C C T34½NR32E</p> <p>1988</p> </div> <p>Set a steel fence post, 5½ ft. long, alongside the stainless steel post.</p> <p>From this corner, the S ¼ sec. cor. of sec. 34, T. 35 N., R. 32 E., monumented with a stainless steel post, 2½ ins. diam., firmly set, exposed 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 35 N., R. 32 E., executed concurrently under this same Group, bears S. 89° 49' W., 16.93 chs. dist.</p> <p>From this same corner, the cor. of secs. 34 and 35, T. 35 N., R. 32 E., monumented with a stainless steel post, 2½ ins. diam., firmly set exposed 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 35 N., R. 32 E., executed concurrently under this same Group, bears N. 89° 49' E., 23.37 chs. dist.</p> <hr/> <p>The point for the N ¼ sec. cor. of sec. 34, is NORTH of the ¼ sec. cor. of secs. 3 and 34, Tps. 34 and 34½ N., Rs. 32 E. and on the S. bdy. of sec. 35, T. 35 N., R. 32 E.</p>