

236

SURVEY OF THE SUBDIVISIONAL LINES,  
T. 34½ N., R. 32 E., MDM, NEVADA

| CHAINS |   |
|--------|---|
|        | <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R32E</p> <p style="text-align: center;"> <math>\frac{1}{4}</math> S 34<br/> <hr style="width: 50px; margin: 0 auto;"/> T34½NR32E </p> <p style="text-align: center;">1988</p> <p>Set a steel fence post, 5½ ft. long, alongside the stainless steel post.</p> <p>From this corner, the cor. of secs. 34 and 35, T. 35 N., R. 32 E., hereinbefore described, bears S. 88° 32' W., 17.58 chs. dist.</p> <p>From this same corner, the S ¼ sec. cor. of sec. 35, T. 35 N., R. 32 E., hereinbefore described, bears N. 88° 32' E., 23.85 chs. dist.</p> <hr/> <p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., monumented with a stainless steel post, 2½ ins. diam., firmly set, exposed 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 34 N., R. 32 E., executed concurrently under this same Group.</p> <p>NORTH, bet. secs. 32 and 33.</p> <p>Over nearly level land, through scattered sagebrush and greasewood.</p> |
| 26.94  | <p>Intersect the S. bdy. of sec. 33, T. 35 N., R. 32 E.</p> <p>Point for the closing cor. of secs. 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R32E</p> <p style="text-align: center;"> S 33<br/> <hr style="width: 50px; margin: 0 auto;"/> S 32   S 33<br/> C C<br/> T34½NR32E </p> <p style="text-align: center;">1988</p>   |