SURVEY OF THE SUBDIVISIONAL LINES, T. 34½ N., R. 32 E., MDM, NEVADA

CHAINS

From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., monumented with a stainless steel post, $2\frac{1}{2}$ ins. diam., firmly set, exposed 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 34 N., R. 32 E., executed concurrently under this same Group.

NORTH, bet. secs. 31 and 32.

Over nearly level land, through scattered sagebrush and greasewood.

27.10 Intersect the S. bdy. of sec. 32, T. 35 N., R. 32 E.

Point for the closing cor. of secs. 31 and 32.

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T35N R32E S 32 S 31 | S 32 C C T34½NR32E

1988

Set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the stainless steel post.

From this corner, the S $\frac{1}{4}$ sec. cor. of sec. 32, T. 35 N., R. 32 E., monumented with a stainless steel post, $2\frac{1}{2}$ ins. diam., firmly set, exposed 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 35 N., R. 32 E., executed concurrently under this same Group, bears S. 89° 18' W., 13.66 chs. dist.

From this same corner, the cor. of secs. 32 and 33, T. 35 N., R. 32 E., monumented with a stainless steel post, $2\frac{1}{2}$ ins. diam., firmly set, exposed 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 35 N., R. 32 E., executed concurrently under this same Group, bears N. 89° 18' E., 26.47 chs. dist.