

SURVEY OF THE SUBDIVISIONAL LINES,
T. 34½ N., R. 32 E., MDM, NEVADA

CHAINS

The point for the N ¼ sec. cor. of sec. 32, is NORTH of the ¼ sec. cor. of secs. 5 and 32, Tps. 34 and 34½ N., Rs. 32 E. and on the S. bdy. of sec. 33, T. 35 N., R. 32 E.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T35N R32E

¼ S 32
T34½NR32E

1988

Set a steel fence post, 5½ ft. long, alongside the stainless steel post.

From this corner, the cor. of secs. 32 and 33, T. 35 N., R. 32 E., hereinbefore described, bears S. 89° 18' W., 14.49 chs. dist.

From this same corner, the point for the S ¼ sec. cor. of sec. 33, T. 35 N., R. 32 E., hereinbefore described, bears N. 89° 18' E., 25.64 chs. dist.

The point for the N ¼ sec. cor. of sec. 31, is NORTH of the ¼ sec. cor. of secs. 6 and 31, Tps. 34 and 34½ N., Rs. 32 E., and on the S. bdy. of sec. 32, T. 35 N., R. 32 E.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T35N R32E

¼ S 31
T34½NR32E

1988

Set a steel fence post, 5½ ft. long, alongside the stainless steel post.