DEPENDENT RESURVEY OF THE SOUTH BOUNDARY, T. 35 N., R. 32 E., MOUNT DIABLO MERIDIAN NEVADA

CHAINS At the corner point Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T35N R32E 5 31 | 5 32 S 31 T34%N R32E 1988 Reset the original wooden post and set a wood post, 3 ins. square. 8 ft. long, alongside the stainless steel post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor. Reestablishment of the Resurvey Executed by H. B. Maxson, U. S. Deputy Surveyor, in 1888; and the Resurveyed by W. H. Craigue, U. S. Surveyor, and N. E. Potter, U. S. Transitman. in 1912 S. 89°45′ W., along the S. bdy. of sec. 31. Over nearly level land, through scattered greasewood. 10.04 The closing cor. of Tps. 34 and 34% N., Rs. 31 and 32 E., monumented with a stainless steel post, 2% ins. diam., firmly set, exposed 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 34 N., R. 31 E., executed concurrently under this same Group. 10.90 Single pole power line, bears N. 40° W. and S. 40° E. Point for the 4 sec. cor. of sec. 31, at 40.21 proportionate distance, there is no remaining evidence of the original corner. POINT NOT MONUMENTED