

SURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 35 NORTH, RANGE 32½ EAST, MDM, NEVADA

CHAINS

Point for the closing cor. of secs. 30 and 31, NORTH, 0.5 lks. from the tangent.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

	T35N		T35N
	R32½E		R33E
CC	S 30		S 30
	S 31		

1988

Set a steel fence post, 5½ ft. long, alongside the stainless steel post.

From this corner, the W ¼ sec. cor. of sec. 30, T. 35 N., R. 33 E., monumented with a stainless steel post, 2½ ins. diam., firmly set showing 4 ins. above ground, with brass cap mkd. as described in the field notes of T. 35 N., R. 33 E., executed concurrently under this same Group, bears N. 0° 30' W., 13.70 chs. dist.

From this same corner, the cor. of secs. 30 and 31, T. 35 N., R. 33 E., monumented with a stainless steel post, 2½ ins. diam., firmly set showing 4 ins. above ground, with brass cap mkd. as described in the field notes of T. 34 N., R. 33 E., executed concurrently under Group No. 654, bears S. 0° 30' E., 27.22 chs. dist.

Land, alkali flat.

Soil, silty alkali.

Undergrowth, shadscale, greasewood and native grass.

Point for the E ¼ sec. cor. of sec. 31, is at midpoint bet. the closing corners and on the W. bdy. of sec. 31, T. 35 N., R. 33 E.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.