

SURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 35 NORTH, RANGE 32½ EAST, MDM, NEVADA

CHAINS	
	T35N R32½E R33E ¼S 31
	1988
	Set a steel fence post, 5½ ft. long, alongside the stainless steel post.
	From this corner, the cor. of secs. 30 and 31, T. 35 N., R. 33 E., hereinbefore described, bears N. 0° 58' W., 12.765 chs. dist.
	From this same corner, the W ¼ sec. cor. of sec. 31, T. 35 N., R. 33 E., monumented with a stainless steel post, 2½ ins. diam., firmly set showing 4 ins. above ground, with brass cap mkd. as described in the field notes of T. 35 N., R. 33 E., executed concurrently under this same Group, bears S. 0° 58' E., 27.34 chs. dist.
	<hr/> From the cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp.
	EAST, bet. secs. 19 and 30, on a transit line describing the tangent.
	Over nearly level land.
40.00	Point for the ¼ sec. cor. of secs. 19 and 30, NORTH, 0.2 lks. from the tangent.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T35N R32½E S 19 ¼ S 30
	1988
	Set a steel fence post, 5½ ft. long, alongside the stainless steel post.
60.75	Intersect the W. bdy. of sec. 19, T. 35 N., R. 33 E.