## SURVEY OF THE SUBDIVISIONAL LINES, TOWNSHIP 35 NORTH, RANGE 32½ EAST, MDM, NEVADA

	TOWNSHIP 35 NORTH, RANGE 32½ EAST, MDM, NEVADA
CHAINS	
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T35N R32½E R33E ¼S 19
	1988
	Set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the stainless steel post.
	From this corner, the cor. of secs. 18 and 19, T. 35 N., R. 33 E., hereinbefore described, bears N. 0° 47' W., 15.515 chs. dist.
	From this same corner, the W ¼ sec. cor. of sec. 19, T. 35 N., R. 33 E., hereinbefore described, bears S. 0° 47' E., 25.545 chs. dist.
	From the cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp.
	EAST, bet. secs. 7 and 18, on a transit line describing the tangent.
	Over nearly level land.
40.00	Point for the ½ sec. cor. of secs. 7 and 18, NORTH, 0.2 lks. from the tangent.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T35N R32½E
	\$\frac{5.7}{5.18}
	1988
	Set a steel fence post, 5½ ft. long, alongside the stainless steel post.
57.56	Intersect the W. bdy. of sec. 7, T. 35 N., R. 33 E.
L	