

SURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 35 NORTH, RANGE 32½ EAST, MDM, NEVADA

CHAINS	
	T35N R32½E R33E ¼S 18
	1988
	Set a steel fence post, 5½ ft. long, alongside the stainless steel post.
	From this corner, the cor. of secs. 7 and 18, T. 35 N., R. 33 E., hereinbefore described, bears N. 1° 08' W., 15.65 chs. dist.
	From this same corner, the W ¼ sec. cor. of sec. 18, T. 35 N., R. 33 E., hereinbefore described, bears S. 1° 08' E., 25.13 chs. dist.
	<hr/> From the cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp.
	EAST, bet. secs. 6 and 7, on a transit line describing the tangent.
	Over nearly level land.
40.00	Point for the ¼ sec. cor. of secs. 6 and 7, NORTH, 0.2 lks. from the tangent.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T35N R32½E S 6 ¼ S 7
	1988
	Set a steel fence post, 5½ ft. long, alongside the stainless steel post.
55.94	Intersect the W. bdy. of sec. 6, T. 35 N., R. 33 E.
	Point for the closing cor. of secs. 6 and 7, NORTH, 0.4 lks. from the tangent.