## 288

## DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY, T. 34 N., R. 33 E., MDM, NEVADA

|        | T. 34 N., R. 33 E., MDM, NEVADA   |
|--------|---|
| CHAINS |   |
| 40.41  | The ¼ sec. cor. of sec. 25, monumented with a volcanic stone, 12X10X4 ins., loosely set in a mound of stone, dimly mkd. ¼.  |
|        | At the corner point   |
|        | Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.                           |
|        | T34N<br>R33E R34E<br>⅓ S 25   |
|        | 1987  |
|        | Deposit the original cornerstone and set a steel fence post, 5½ ft. long, alongside the stainless steel post.   |
|        | N. 0° 17' E., beginning new measurement.  |
| 2.16   | The closing cor. of secs. 30 and 31, T. 34 N., R. 34 E., monumented with a trapstone, 8X8X2 ins., loosely set in a mound of stone, plainly mkd. with 5 notches on N. edge and 1 notch on S. edge. |
|        | At the corner point   |
|        | Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.   |
|        | T34N<br>R33E R34E<br> S 30 C<br>S 25 S 3T C   |
|        | 1987  |
|        | Deposit the original cornerstone and set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the stainless steel post.   |
| 5.00   | Wash, 20 1ks. wide, 3 ft. deep, drains SW.  |
|        |   |
|        |   |
|        |   |
|        |   |
|        |   |