

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 34 N., R. 33 E., MDM, NEVADA

CHAINS	
	<p>From this same corner, the SW. cor. of a barn, 30 lks. wide, 39 lks. long, inside fenced area, bears S. 32° 21' W., 20.83 chs. dist.</p> <p>From this same corner, the SW. cor. of a shed, 41 lks. wide, 60 lks. long, inside fenced area, bears S. 33° 43' W., 26.51 chs. dist.</p> <p>From this same corner, the SW. cor. of an equipment shed, 31 lks. wide, 99 lks. long, inside fenced area, bears S. 24° 33' W., 25.60 chs. dist.</p> <p>From this same corner, the SW. cor. of Danners' house, 95 lks. wide, 99 lks. long, inside fenced area, bears S. 14° 53' W., 27.19 chs. dist.</p> <p>From this same corner, the SW. cor. of root cellar, 19 lks. wide, 28 lks. long, inside fenced area, bears S. 11° 44' W., 26.75 chs. dist.</p>
	<p>N. 5° 01' W., along the E. bdy. of sec. 1.</p> <p>Over mountainous land, through scattered sagebrush, native grass and heavy juniper.</p>
19.87	The W ¼ sec. cor. of sec. 1, T. 34 N., R. 33½ E., monumented with a stainless steel post, 2½ ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the survey of the subdivisional lines of T. 34 N., R. 33½ E., executed concurrently under this same Group.
25.70	Ridge, bears ENE. and WSW.
39.95	<p>Point for the ¼ sec. cor. of secs. 1 and 6, at proportionate distance, based on the 1875 survey; there is no remaining evidence of the original corner. Hereafter this corner will refer to the E ¼ sec. cor. of sec. 1 only.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p>