## DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES, TOWNSHIP 35 NORTH, RANGE 33 EAST, MDM, NEVADA

## CHAINS

From this corner, the  $\frac{1}{4}$  sec. cor. of secs. 12 and 13, hereinbefore described, bears S. 0° 02' W., 16.83 chs. dist.

From this same corner, the S  $\frac{1}{4}$  sec. cor. of sec. 1, hereinbefore described, bears N. 0° 02' E.

Point for the E  $\frac{1}{4}$  sec. cor. of sec. 12, is at the intersection of the E-W center line of sec. 12 with the W. bdy. of sec. 7, T. 35 N., R. 34 E.

Set a stainless steel post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T35N R33E R34E ¼ | S 12|

1988

Set a steel fence post,  $5\frac{1}{2}$  ft. long, alongside the stainless steel post.

From this corner, the  $\frac{1}{4}$  sec. cor. of secs. 11 and 12, hereinbefore described, bears S. 87° 46' W., 23.27 chs. dist.

From this same corner, the amended monument for the E  $\frac{1}{4}$  sec. cor. of sec. 12, hereinbefore described, bears N. 87° 46' E.

N. 0° 39' W., bet. secs. 1 and 2.

Over nearly level land, covered with medium shadscale, scattered greasewood and native grass.

- 18.20 | Trail road, bears irregularly ESE. and WNW.
- Point for the 1/2 sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.