13

SURVEY OF THE SUBDIVISIONAL LINES, TOWNSHIP 35½ NORTH, RANGE 33 EAST, MDM, NEVADA

	TOWNSHIP 35% NURTH, RANGE 33 EAST, MDM, NEVADA
CHAINS	
	T36N R33E
	1988
	Set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the stainless steel post.
	From this corner, the standard corner of Tps. 36 N., Rs. 33 and 34 E., hereinbefore described, bears N. 89° 43' E., 16.67 chs. dist.
	Land, rolling sand hills. Soil, sandy loam. Undergrowth, sagebrush, whitesage and native grass.
	From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., monumented with a stainless steel post, 2½ ins. diam., firmly set, showing 4 ins. above ground, with brass cap mkd. as described in the field notes of T. 35 N., R. 33 E., executed concurrently under this same Group.
	NORTH, bet. secs. 34 and 35.
	Over nearly level land, changing to rolling sand hills.
20.19	Intersect the Seventh Standard Parallel North.
	Point for the closing cor. of secs. 34 and 35.
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T36N R33E S 35 S 34 S 35 T35½N R33E C C
	1988