SURVEY OF THE SUBDIVISIONAL LINES, TOWNSHIP 35½ NORTH, RANGE 33 EAST, MDM, NEVADA

CHAINS

Set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the stainless steel post.

From this corner, the standard cor. of secs. 35 and 36, T. 36 N., R. 33 E., hereinbefore described, bears N. 89° 47′ E., 17.62 chs. dist.

Land, nearly level to rolling sand hills.
Soil, silty alkali to sandy loam.
Undergrowth, shadscale, halogeten, sagebrush and native grass.

Point for the N $\frac{1}{4}$ sec. cor. of sec. 35, is at midpoint bet. closing corners and on the S. bdy. of sec. 36, T. 36 N., R. 33 E.

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T36N R33E

¼ S 35 T35½N R33E

1988

Set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the stainless steel post.

From this corner, the standard ½ sec. cor. of sec. 36, T. 36 N., R. 33 E., hereinbefore described, bears N. 89° 47' E., 16.865 chs. dist.

From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., monumented with a stainless steel post, $2\frac{1}{2}$ ins. diam., firmly set, showing 4 ins. above ground, with brass cap mkd. as described in the field notes of T. 35 N., R. 33 E., executed concurrently under this same Group.

NORTH, bet. secs. 33 and 34.