SURVEY OF THE SUBDIVISIONAL LINES, TOWNSHIP 35½ NORTH, RANGE 33 EAST, MDM, NEVADA

CHAINS

Point for the N $\frac{1}{2}$ sec. cor. of sec. 33, is at midpoint bet. closing corners and on the S. bdy. of sec. 34, T. 36 N., R. 33 E.

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T36N R33E

¼ S 33 T35½N R33E

1988

Set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the stainless steel post.

From this corner, the standard ½ sec. cor. of sec. 34, T. 36 N., R. 33 E., hereinbefore described, bears N. 89° 55' E., 19.165 chs. dist.

From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., monumented with a stainless steel post, $2\frac{1}{2}$ ins. diam., firmly set, showing 4 ins. above ground, with brass cap mkd. as described in the field notes of T. 35 N., R. 33 E., executed concurrently under this same Group.

NORTH, bet. secs. 31 and 32.

Over nearly level land.

25.08

Intersect the Seventh Standard Parallel North.

Point for the closing cor. of secs. 31 and 32.

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T36N R33E S 32 S 31|S 32 T35½N R33E C C

1988