

TOWNSHIP 34 NORTH, RANGE 33½ EAST, MDM, NEVADA

CHAINS

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, the Special Instructions dated September 4, 1987 and the Supplemental Special Instructions dated December 17, 1987.

The directions of the lines of the survey were determined by azimuth taken from U.S.C. & G.S. triangulation stations "BONIT" located in section 27, T. 34 N., R. 33 E., and "EUGENE 2 (USGS)" located in section 17, T. 34 N., R. 34 E. The direction of the lines were carried forward throughout the township by sustained angulation.

The vertical angles of measurements made on the slope were ascertained with a theodolite in good adjustment; the horizontal equivalents only are entered in the field notes.

The geographic position of the cor. of secs. 24 and 25, T. 34 N., R. 33 E. and sec. 24, T. 34 N., R. 33½ E., is at latitude 40° 47' 29.5" N. and longitude 118° 11' 52.9" W., (NAD 27), as calculated from U.S.C. & G.S. triangulation station "EUGENE 2 (USGS)."

The mean magnetic declination was found to be 16° E.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 35 N., R. 34 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
H.B. Maxson, U.S. Deputy Surveyor,
in 1888
and the Resurvey Executed by
F.H. Criss, U.S. Deputy Surveyor,
in 1901.

The cor. of secs. 31 and 32, monumented with a trap stone, 16X14X5 ins., plainly mkd. with 5 notches on E. edge and 1 notch on W. edge, firmly set in a mound of stone.

At the corner point