DEPENDENT RESURVEY OF THE SEVENTH STANDARD PARALLEL NORTH, THROUGH A PORTION OF RANGE 35 EAST, MOUNT DIABLO MERIDIAN, NEVADA CHAINS DEPENDENT RESURVEY OF THE SEVENTH STANDARD PARALLEL NORTH, THROUGH A PORTION OF RANGE 35 EAST, MOUNT DIABLO MERIDIAN, NEVADA Reestablishment of the Survey Executed by W. Epler, U.S. Deputy Surveyor in 1867. The standard ½ sec. cor. of sec. 31, monumented with a basalt stone, 13X9X6 ins., mkd. ½ on N. face, firmly set in a mound of stone, with a steel fence post, 5½ ft. long, firmly set, showing $3\frac{1}{2}$ ft. above the ground alongside the cornerstone. At the corner point Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. SC T36N R35E 1₄ S 31 1988 Deposit the original cornerstone and reset the steel fence post alongside the stainless steel post and rebuild the mound of stone, 3 ft. base, 2 ft. high, N. of cor. S. 89° 43' W., along the S. bdy. of sec. 31. Over rolling sand hills, covered with medium rabbitbrush, native grass, scattered greasewood and whitesage. 36.27 The closing cor. of Tps. 34 N., Rs. 34 and 35 E., hereinafter described. 40.24 The standard cor. of Tps. 36 N., Rs. 34 and 35 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, showing 4 ins. above ground, with brass cap mkd. as described in the field notes of T. 36 N., R. 34 E., executed under Group No. 532.

49