DEPENDENT RESURVEY OF THE SEVENTH STANDARD PARALLEL NORTH, THROUGH RANGE 34 EAST, MOUNT DIABLO MERIDIAN, NEVADA

	MOUNT DIABLO MERIDIAN, NEVADA
CHAINS	
	S. 89° 38' W., along the S. bdy. of sec. 32.
	Over nearly level land, through shadscale and sagebrush.
16.80	Trail road, bears N. and S.
40.06	The standard 1/4 sec. cor. of sec. 32, monumented with an iron post, 21/2 ins. diam., firmly set, showing 6 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 36 N., R. 34 E., executed under Group No. 532.
	From this corner, U.S.C. & G.S. triangulation station "RANCH," monumented with a standard bronze disk mkd. RANCH 1958, firmly set in the top of a 10 ins. square concrete monument, exposed 14 ins. above ground, bears N. 42° 22' W., 16.745 chs. dist.
	S. 89° 37' W., beginning new measurement.
	Over nearly level land.
35.50	The closing cor. of secs. 5 and 6, monumented with an iron post, $2\frac{1}{2}$ ins diam., firmly set, showing 6 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 36 N., R. 34 E., executed under Group No. 532.
40.07	The standard cor. of secs. 31 and 32, monumented with an iron post, 2½ ins. diam., firmly set, showing 6 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 36 N., R. 34 E., executed under Group No. 532.
	From this corner, U.S.C. & G.S. triangulation station "RANCH," hereinbefore described, bears N. 66° 18' E., 31.44 chs. dist.
	From this same corner, U.S.G.S. Bench Mark, monumented with a standard brass tablet set on a copper weld rod in a fiberglass cylinder, 6 ins. diam., set flush with the ground, with brass tablet mkd. "I STR 1977," bears N. 7° 40' W., 4.79 chs. dist.
	1