

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 35 N., R. 34 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

From this corner, the standard $\frac{1}{4}$ sec. cor. of sec. 31, T. 36 N., R. 34 E., hereinbefore described, bears S. $89^{\circ} 44'$ W., 5.15 chs. dist.

Point for the S $\frac{1}{4}$ sec. cor. of sec. 6, is at the intersection of the N-S center line of sec. 6 with the N. bdy. of sec. 1, T. 35 N., R. 33 E.

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T35N R34E
 $\frac{1}{4}$ S 6
T35N R33E

1988

Set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the stainless steel post.

From this corner, the N $\frac{1}{4}$ sec. cor. of sec. 6, hereinbefore described, bears N. $0^{\circ} 50'$ W., 18.92 chs. dist.

From this same corner, the N $\frac{1}{4}$ sec. cor. of sec. 7, hereinbefore described, bears S. $0^{\circ} 50'$ E.

Point for the W $\frac{1}{4}$ sec. cor. of sec. 6, is at the intersection of the E-W center line of sec. 6 with the E. bdy. of sec. 1, T. 35 N., R. 33 E.

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T35N
R33E R34E
| $\frac{1}{4}$
| S 6

1988