

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,  
T. 24 N., R. 60 E., MDM, NEVADA

Chains

Reestablishment of the Survey Executed by F. Bell  
and D.G. Bell, U.S. Deputy Surveyors,  
in 1883.

From the cor. of Tps. 23 and 24 N., Rs. 60 E., monumented with a stainless steel post, 2½ ins. diam., firmly set showing 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 23 N., R. 60 E., executed concurrently under this same Group.

N. 0° 40' E., along the E. bdy. of sec. 36.

Over nearly level land, covered with scattered sagebrush and greasewood.

- 1.00 Trail road, bears NNW. and SSE.
- 23.10 Trail road, bears E. and W.
- 26.575 The W ¼ sec. cor. of sec. 31, T. 24 N., R. 61 E., hereinafter described.
- 39.70 Improved road, bears NE. and SW.
- 40.96 The E ¼ sec. cor. of sec. 36, monumented with a sharpened squared wooden post, 2 ins. diam., 26 ins. long, plainly mkd. ¼ on the W. face and loosely set in a mound of earth.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground with magnet at base, with brass cap mkd.

T24N  
R60E R61E  
¼ |  
S 36 |

1991

Reset the original wooden post and set a steel fence post, 5½ ft. long, alongside the stainless steel post.

From this corner, U.S.G.S. Bench Mark, monumented with a standard brass tablet on copperweld, set flush with ground, with cap mkd. "ELEV 6258FT 239MDC 1975", with mound of stone W., 3 ft. base, 2 ft. high, bears N. 38° 27' E., 20.36 chs. dist.