DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 24 N., R. 61 E., MDM, NEVADA

Chains

Reestablishment of the Survey Executed by F. Bell
and D. G. Bell, U.S. Deputy Surveyors,
in 1883

From the ¼ sec. cor. of secs. 1 and 36, monumented with an unmarked granite stone, 14X10X8 ins., firmly set 4 ins. in the ground, with a mound of stone NE. of cor. This granite stone is accepted as the best available evidence of the original cor. position. The bearing trees of record were not found.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to solid rock with magnet at base, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

T24N R61E
S 36
¼ ———
S 1
T23N R61E

1991

Deposit the unmarked granite stone alongside the stainless steel post.

S. 89° 16′ W., bet. secs. 1 and 36.

Over rolling to mountainous land, covered with pinon pine and juniper timber and scattered sagebrush and greasewood.

4.40 Improved gravel road, bears ENE. and WSW.

16.20 Spur, slopes S.

39.24 Point for the cor. of secs. 1, 2, 35 and 36, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 28 ins. flush with the ground with magnet at base, with brass cap mkd.