SURVEY OF PARCEL F, SECTION 5,
TOWNSHIP 11 NORTH, RANGE 21 EAST, MDM, NEVADA

FEET	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground with a magnet at base, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	
	1991
	Cor. is located on steep, rocky, NE slope.
	S. 54°49'20" E., on line 3-4, Parcel F, identical with a portion of line 2-1, Parcel L.
360.00	Angle Point No. 4, Parcel F, identical with Angle Point No. 3, Parcel E, hereinbefore described.
	N. 35°10'40" E., on line 4-1, Parcel F, identical with line 3-2, Parcel E.
638.34	Angle Point No. 1, Parcel F, identical with Angle Point No. 2, Parcel E, and place of beginning.

SURVEY OF PARCEL G, SECTION 5,
TOWNSHIP 11 NORTH, RANGE 21 EAST, MDM, NEVADA

	Beginning at Angle Point No. 1, Parcel G, identical with Angle Point No. 2, Parcel F, on the southerly right-of-way bdy. of U.S. Highway 395, in curve, hereinbefore described.
	Thence on line 1-2, Parcel G, identical with a portion of line 8-7, Parcel D, on the southerly right-of-way bdy. of U.S. Highway 395, along the arc of a curve to left having a radius of 4925.00 ft.; the chord of said arc bears N. 51°14'43" W., 340.66 ft. dist.
340.73	Angle Point No. 2, Parcel G, identical with Angle Point No. 1, Parcel H, hereinbefore described.
	S. 35°10'40" W., on line 2-3, Parcel G, identical with line 1-5, Parcel H.
708.09	Point for Angle Point No. 3, Parcel G, identical with Angle Point No. 5, Parcel H.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground with a magnet at base, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.