DEPENDENT RESURVEY OF THE FIFTH STANDARD PARALLEL SOUTH, THROUGH A PORTION OF RANGE 58 EAST, MDM, NEVADA

CHAINS 19.50	Red Rock Scenic Drive, oiled, bears NNE. and SSW.
32.10	Red Rock Scenic Drive, oiled, bears SSE. and NNW.
40.642	The standard $\frac{1}{4}$ sec. cor. of sec. 35, monumented with a basalt stone, 17x8x6 ins., firmly set 8 ins. in the ground, mkd. $\frac{1}{4}$ on N. face, with a mound of stone N.
	At the corner point
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground, over a DEEP-1 magnetic marker and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	SC T20S R58E ½ S 35
	1992
	Deposit the original cornerstone alongside the stainless steel post.
	DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY OF TOWNSHIP 21 SOUTH, RANGE 58 EAST, MOUNT DIABLO MERIDIAN, NEVADA
	Reestablishment of the Survey Executed by J. M. Brunt and W. H. Proctor, U. S. Deputy Surveyors in 1881 and the Resurvey Executed by Cadastral Surveyor P. K. Russell in 1957.
	From the true point for the cor. of secs. 1, 6, 7 and 12. From which the witness cor. bears N. 85° 41' W., 1.01 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of T. 21 S., R. 59 E., executed under Group No. 642.
	N. 1° 37.6' W., bet. secs. 1 and 6.
	Over broken sandstone ledges.
11.00	Summit of Calico Hills, ridge, bears SE. and NW.
20.053	Point for the S $^{1}/_{16}$ sec. cor. of secs. 1 and 6, identical with Angle Point No. 5, Parcel C, sec. 6, T. 21 S., R. 59 E., at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground, over a DEEP-1 magnetic marker and in a mound of stone, 3 ft. base to top, with brass cap mkd.