

299

DEPENDENT RESURVEY OF A PORTION OF THE  
SUBDIVISION OF SECTION 6,  
T. 21 S., R. 59 E., MDM, NEVADA

CHAINS	
	<p>N. 85° 35.6' W., on a portion of the E-W center line of sec. 6. Over rolling land.</p>
19.714	<p>The C-W 1/16 sec. cor. of sec. 6, identical with Angle Point No. 1, Parcel C, sec. 6, monumented with an iron post, 2<sup>1</sup>/<sub>2</sub> ins. diam., firmly set in a mound of stone, 2 ft. base, 1 ft. high, with brass cap mkd. as described in the field notes of T. 21 S., R. 59 E., executed under Group No. 362. Add marks 1992 to brass cap.</p> <p>From this corner, U.S.G.S. triangulation station "RED", monumented with a standard brass tablet set in concrete, with brass tablet mkd. "RED 1950," bears S. 67° 15.4' E., 271.586 chs. dist.</p>
	<hr/> <p>N. 85° 35.6' W., beginning new measurement.</p>
0.456	<p>Angle Point No. 3, Parcel C, sec. 6, hereinafter described.</p>
19.792	<p>The <sup>1</sup>/<sub>4</sub> sec. cor. of secs. 1 and 6, on the W. bdy. of the Tp., identical with Angle Point No. 4, Parcel C, sec. 6, monumented with an iron post, 2<sup>1</sup>/<sub>2</sub> ins. diam., firmly set, exposed 8 ins. above the ground, with brass cap mkd. as described in the field notes of T. 21 S., R. 58 E., executed concurrently under this same Group.</p>
<hr/> <p>SUBDIVISION OF THE SOUTHWEST <sup>1</sup>/<sub>4</sub> OF SECTION 6, T. 21 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>	
	<p>From the W 1/16 sec. cor. of secs. 6 and 7, monumented with an iron post, 2<sup>1</sup>/<sub>2</sub> ins. diam., firmly set, exposed 8 ins. above the ground, with brass cap mkd. as described in the field notes of T. 21 S., R. 59 E., executed under Group No. 642. Add marks 1992 to brass cap.</p>
	<p>N. 1° 16.3' W., on the N-S center line of the SW <sup>1</sup>/<sub>4</sub> of sec. 6. Over rolling land.</p>
3.50	<p>Gravel road, 50 lks. wide, bears NE. and SW.</p>
19.998	<p>A rebar, <sup>5</sup>/<sub>8</sub> in. diam., firmly set, exposed 2 ins. above ground, with aluminum cap mkd. RLS 4145.</p>
20.364	<p>Point for the SW 1/16 sec. cor. of sec. 6, identical with Angle Point No. 6, Parcel C, sec. 6, at intersection with the E-W center line of the SW <sup>1</sup>/<sub>4</sub>.</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 20 ins. in the ground, over a DEEP-1 magnetic marker and in a collar of stone, with brass cap mkd.</p>
<p>SW 1/16 S 6 1992</p>	