

332

DEPENDENT RESURVEY OF THE WEST BOUNDARY
(HUMBOLDT RIVER GUIDE MERIDIAN)
T. 24 N., R. 36 E., MDM, NEVADA

CHAINS

DEPENDENT RESURVEY OF THE WEST BOUNDARY
(HUMBOLDT RIVER GUIDE MERIDIAN)
T. 24 N., R. 36 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed
by W. Epler, U.S. Deputy Surveyor, in 1867.

The cor. of Tps. 23 and 24 N., Rs. 35 and 36 E., monumented with the decayed remains of a wood post, with illegible scribe marks visible, lying loosely alongside an iron pipe, 1 in. diam., 14 ins. long, firmly set, showing 4 ins. above ground.

At the corner point

Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 24 ins. in the ground, with brass cap mkd.

| | | |
|--------|--|--------|
| T 24 N | | |
| R 35 E | | R 36 E |
| S 36 | | S 31 |
| | | |
| S 1 | | S 6 |
| T 23 N | | |
| 1991 | | |

Reset the decayed remains of the original wood post alongside the stainless steel post, insert the iron pipe inside the stainless steel post and raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

From this corner, the ¹/₄ sec. cor. of secs. 1 and 36, Tps. 23 and 24 N., Rs. 35 E., identical with U.S.G.S. triangulation station, "SEC COR 1-1/4N/23N/35E", monumented with an iron post, 1 in. diam., firmly set, showing 10 ins. above the ground, with brass cap mkd. as described in the field notes of T. 23 N., R. 35 E., executed under Group No. 153, bears S. 87° 35' W., 30.50 chs. dist.

N. 0° 03' E., bet. secs. 31 and 36.

Over rolling land, covered with medium greasewood, scattered shadscale, rabbitbrush and native grass.

38.40 Enter alkali flat.

40.03 The ¹/₄ sec. cor. of secs. 31 and 36, monumented with a volcanic stone, 11x6x4 ins., firmly set in a deeply embedded mound of stone, dimly mkd. ¹/₄ on N. face.

At the corner point

Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 24 ins. in the ground, with brass cap mkd.