

DEPENDENT RESURVEY OF THE WEST BOUNDARY  
(HUMBOLDT RIVER GUIDE MERIDIAN)  
T. 24 N., R. 36 E., MDM, NEVADA

CHAINS	
	<div style="text-align: center;"> T24N  R35E R36E  S 1 S 6  <hr/> S 12 S 7  1991 </div> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <hr/> <p>N. 2° 42' W., bet. secs. 1 and 6.</p> <p>Over mountainous land, covered with medium pinion pine, scattered juniper, sagebrush, greasewood and native grass.</p> <p>1.00 Ridge, bears ESE. and WNW.</p> <p>11.00 Trail road, bears SSE. and NNW.</p> <p>32.00 Creek, 5 lks. wide, 3 ins. deep, course irregularly SE.</p> <p>40.83 The <math>\frac{1}{4}</math> sec. cor. of secs. 1 and 6, monumented with a trapstone, 14x8x5 ins., firmly set 7 ins. in the ground, with a mound of stone to the S., mkd. <math>\frac{1}{4}</math> on N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> T24N  R35E R36E  <math>\frac{1}{4}</math>  S 1 S 6  1991 </div> <p>Deposit the original cornerstone alongside the stainless steel post and rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <hr/> <p>N. 0° 10' W., beginning new measurement.</p> <p>Over mountainous land.</p> <p>39.46 Point for the cor. of Tps. 24 and 25 N., Rs. 35 and 36 E., at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 4 ins. in the ground to solid rock and in a mound of stone, 5 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> T25N  R35E R36E  S 36 S 31  <hr/> S 1 S 6  T24N  1991 </div>