

350

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,  
(HUMBOLDT RIVER GUIDE MERIDIAN)  
T. 25 N., R. 36 E., MDM, NEVADA

|                         |   |
|-------------------------|---|
| <p>CHAINS<br/>39.46</p> | <p>The <math>\frac{1}{4}</math> sec. cor. of secs. 25 and 30, monumented with a volcanic stone, 14x7x6 ins., firmly set 7 ins. in the ground, plainly mkd. <math>\frac{1}{4}</math> on N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T25N<br/>R35E R36E<br/><math>\frac{1}{4}</math><br/>S 25   S 30<br/>1991</p> <p>Deposit the original cornerstone alongside the stainless steel post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>From this corner, Reference Mark No. 2 for U.S.G.S. triangulation station "STILLWATER", monumented with a standard brass tablet, cemented in a rock outcrop, mkd. "NO 2 1953" and an arrow pointing towards the destroyed station, bears N. <math>57^{\circ} 05'</math> W., 100.54 chs. dist.</p> |
|                         | <p style="text-align: center;">DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,<br/>T. 25 N., R. 36 E., MOUNT DIABLO MERIDIAN, NEVADA</p>  |
|                         | <p style="text-align: center;">Reestablishment of the Survey Executed by<br/>G. W. Conkling, Jr. and T. K. Stewart,<br/>U.S. Deputy Surveyors, in 1881.</p>   |
|                         | <p>From the cor. of Tps. 24 and 25 N., Rs. 36 and 37 E., monumented with an aluminum post, <math>2\frac{1}{2}</math> ins. diam., firmly set in a mound of stone, with an aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 24 N., R. 37 E., executed under Group No. 593.</p> <p>N. <math>89^{\circ} 14'</math> W., bet. secs. 1 and 36.</p> <p>Over mountainous land, covered with scattered greasewood, Brigham tea, shadscale, juniper and native grass.</p>   |
| <p>4.70</p>             | <p>Spur, slopes S.</p>  |
| <p>41.12</p>            | <p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 4 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T25N R36E<br/>S 36<br/><math>\frac{1}{4}</math> ———<br/>S 1<br/>T24N<br/>1991</p>   |