

## TOWNSHIP 2 NORTH, RANGE 42 EAST, MDM, NEVADA

CHAINS	
	<p>The direction of lines of this survey were determined by azimuth taken from U. S. C. &amp; G. S. triangulation station "GOLDEN", located in section 1 and carried forward by sustained angulation throughout the progress of the survey.</p> <p>The vertical angles of measurements made on the slope were ascertained with a theodolite in good adjustment; the horizontal equivalents only are entered in the field notes.</p> <p>The geographic position of the center <math>\frac{1}{4}</math> section corner of section 1 is at latitude <math>38^{\circ} 03' 26.01''</math> N. and longitude <math>117^{\circ} 12' 44.91''</math> W. (NAD 1927) as calculated from a direct tie to U. S. C. &amp; G. S. triangulation station "GOLDEN".</p> <p>The mean magnetic declination was found to be <math>15\frac{1}{2}^{\circ}</math> E.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 2 N., R. 42 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of the Resurvey Executed by D. R. Beck, Cadastral Surveyor, in 1972-73.</p> <hr/> <p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 1 and 12, monumented with a brass tablet, <math>3\frac{1}{4}</math> ins. diam., seated in concrete in solid rock, with top mkd. as described in the field notes of T. 2 N., R. 42 E., executed under Group No. 487.</p> <p>N. <math>87^{\circ}51'</math> W. bet. secs. 1 and 12.</p> <p>Over gently rolling land, covered with shadscale and sagebrush.</p> <p>9.922 Point for the E-W <math>\frac{1}{64}</math> sec. cor. of secs. 1 and 12.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 1 E-W <math>\frac{1}{64}</math> ----- S 12  1990</p> </div> <p>Set a steel fence post, <math>5\frac{1}{2}</math> ft. long, alongside the stainless steel post.</p> <p>10.50 U. S. Highway No. 95, curving from NNW to SSW.</p> <p>19.844 The W <math>\frac{1}{16}</math> sec. cor. of secs. 1 and 12, monumented with a rebar, of unknown origin, <math>\frac{5}{8}</math> in. diam., 18 ins. long, firmly set flush with the ground and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p>