

195

DEPENDENT RESURVEY OF A PORTION OF
MINERAL SURVEY NO. 2132,
T. 2 N., R. 42 E., MDM, NEVADA

CHAINS	
11.395	<p>Thence S. 86°21' E., on line 4-3, Molly Gibson lode.</p> <p>Cor. No. 3 of M. S. No. 2132, Molly Gibson lode, monumented with a pine post, 4 ins. square, 24 ins. long, lying loose on a mound of stone, mkd. 2132.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">MG-3 MS 2132 —●— S1 T2NR42E 1990</p> <p>Reset the original wooden post alongside the stainless steel post.</p>
<hr/> <p>SUBDIVISION OF SECTION 1, T. 2 N., R. 42 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>	
9.939	<p>From the ¼ sec. cor. of secs. 1 and 12.</p> <p>N. 0°36' E., on the N-S center line of sec. 1.</p> <p>Point for the C-S-S 1/64 sec. cor. of sec. 1.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SS 1/64 C S1 C</p> <p style="text-align: center;">1990</p> <p>Set a steel fence post, 5½ long, alongside the stainless steel post.</p>
19.878	<p>The C-S 1/16 sec. cor. of sec. 1, established by Kenneth L. Haskew, R.L.S. No. 3849, in 1980, monumented with a rebar, 1 in. diam., 18 ins. long, firmly set, showing 2 ins. above ground, with a brass tag attached mkd. RLS 3849, and is accepted as a careful and faithful determination of the position of the corner, with a rebar, 5/8 in. diam., firmly set, showing 2 ins. above ground, with a plastic cap mkd. RLS 2518 alongside.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>