

208

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 19 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

T20N R31E

S 36

 $\frac{1}{4}$

S 1

T19N

1992

Deposit the original cornerstone and galvanized pipe and set a steel fence post, 5½ ft. long, alongside the stainless steel post.

This corner is located 3 lks. S. of a fence; fence bears E. and W.

N. 89°49' W., beginning new measurement.

Over nearly level land.

40.10

The cor. of secs. 1, 2, 35 and 36, monumented with a basalt stone, 16X9X6 ins., plainly mkd. with 5 notches on W. edge and 1 notch on E. edge, set flush with ground.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, over a DEEP-1 magnetic marker, with brass cap mkd.

T20N R31E

S 35 | S 36

S 2 | S 1

T19N

1992

Deposit the original cornerstone and set a steel fence post, 5½ ft. long, alongside the stainless steel post.

From this corner, a fence corner bears N. 45° W., 0.05 chs. dist., from which fences bear S. and E.

DEPENDENT RESURVEY OF A PORTION OF THE
SUBDIVISIONAL LINES,
T. 19 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
E. B. Monroe, U.S. Deputy Surveyor, in 1868.

The cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., monumented with a basalt stone, 10X8X6 ins., firmly set in a mound of stone, plainly mkd. with 3 grooves on E. and W. faces, and a redwood post 3X4 ins., firmly set showing 12 ins. above ground alongside.

At the corner point