

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

T19N R31E
S 28
—
S 33

1992

Deposit the original cornerstone and set a steel fence post, 5½ ft. long, alongside the stainless steel post and rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of cor.

From this corner, U.S.C. & G.S. triangulation station "LAKE", monumented with a standard brass tablet stamped LAKE 1958 cemented flush in 3 ft. diam. boulder showing 3 ins. above ground, bears N. 20°37' E., (Mean Bearing) 86.85 chs. dist.

INDEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 19 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

This Independent Resurvey Supersedes the Survey Executed by
E. B. Monroe, U.S. Deputy Surveyor, in 1868.

The corners were established on the latitudinal curve between the orig. southeast Tp. cor. and the orig. cor. of secs. 3, 4, 33 and 34, and at 40 and 80 ch. intervals from the southeast Tp. cor.

The cor. of Tps. 18 and 19 N., Rs. 31 and 32 E., monumented with a basalt stone, 15X12X8 ins., firmly set in a mound of stone, plainly mkd. with 6 notches on N., S., E. and W. edges with a steel fence post, firmly set showing 3 ft. above ground alongside. This cor. will now refer to the cor. of Tps. 18 and 19 N., Rs. 31 E. only.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, over a DEEP-1 magnetic marker, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T19N
R31E R32E
S 36
—
S 1
T18N

1992

From this corner, U.S.C. & G.S. triangulation station "STILLWATER", monumented with a standard brass tablet stamped STILLWATER 1935 cemented flush in 2 ft. diam. boulder showing 4 ins. above ground, bears S. 81°52' W., (Mean Bearing) 36.94 chs. dist.

S. 89°54' W., bet. secs. 1 and 36, on a transit line describing the tangent.