

235

DEPENDENT RESURVEY OF THE FOURTH STANDARD PARALLEL NORTH,
THROUGH A PORTION OF RANGE 32 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

DEPENDENT RESURVEY OF THE FOURTH STANDARD PARALLEL NORTH,
THROUGH A PORTION OF RANGE 32 EAST, MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
W. Epler, U.S. Deputy Surveyor, in 1865.

The standard cor. of secs. 34 and 35, monumented with a splintered wooden post, 14 ins. long, wired to 1 in. galvanized pipe, lying loose on the ground, with illegible scribe marks visible.

At the corner point

Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 24 ins. in the ground, over a DEEP-1 magnetic marker, with brass cap mkd.

S C
T21N R32E
S 34 | S 35

1992

Deposit the original wooden post and galvanized pipe alongside the stainless steel post.

From this corner, a fence corner bears S. 45° E., 0.05 chs. dist., from which fences bear N. and W.

From this same corner, a ⁵/₈ in. rebar, with 2 in. aluminum cap mkd. 4113, bears S. 74°36' E., 1.43 chs. dist.

N. 88°36' W., along the S. bdy. of sec. 34.

Over nearly level land, covered with scattered sagebrush and native grass.

30.31 The closing cor. of secs. 2 and 3, T. 20 N., R. 32 E., hereinafter described.

39.96 The standard ¹/₄ sec. cor. of sec. 34, monumented with a sharpened wooden post, 1X3 ins., 30 ins. long, lying loose on the ground, with illegible scribe marks visible.

At the corner point

Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 24 ins. in the ground, over a DEEP-1 magnetic marker, with brass cap mkd.

S C
T21N R32E
¹/₄ S 34

1992