

236

DEPENDENT RESURVEY OF THE FOURTH STANDARD PARALLEL NORTH,
THROUGH A PORTION OF RANGE 32 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

Reset the original wooden post and set a steel fence post, 5½ ft. long, alongside the stainless steel post.

From this corner, U.S.C. & G.S. Bench Mark mkd. "F 389 1955", hereinafter described, bears S. 6°09' E., (Mean Bearing) 138.21 chs. dist.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 20 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
E. B. Monroe, U.S. Deputy Surveyor, in 1868.

From the cor. of Tps. 19 and 20 N., Rs. 31 E., monumented with a stainless steel post, 2½ ins. diam., firmly set showing 4 ins. above ground, with brass cap mkd. as described in the field notes of T. 19 N., R. 31 E., executed concurrently under this same Group.

N. 0°02' E., along the E. bdy. of sec. 36.

Over nearly level land, covered with scattered shadscale and native grass.

30.81 The W ¼ sec. cor. of sec. 31, T. 20 N., R. 32 E., hereinafter described.

39.96 The ¼ sec. cor. of secs. 31 and 36, rehabilitated by G. L. Ducret, U.S. Fish and Wildlife Service, in 1950, monumented with a rusted galvanized pipe, 18 ins. below the surface of ground, with an unmarked basalt stone, 8X6X5 ins., lying loose on the ground, from which the only remaining 1950 accessory:

A wood post, 4 ins. square, firmly set showing 24 ins., bears NORTH, 15 lks. dist.

This cor. will now refer to sec. 36 only.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, over a DEEP-1 magnetic marker, with brass cap mkd.

T20N
R31E | R32E
1/4
S 36 |

1992

Deposit the galvanized pipe and basalt stone alongside the stainless steel post.

This corner is located 3 lks. E of a fence; fence bears N. and S.