	DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY, T. 20 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA
CHAINS	N. 0°02' E., beginning new measurement.
	Over nearly level land.
16.00	Improved gravel road, bears ENE. and WSW.
30.86	The closing cor. of secs. 30 and 31, T. 20 N., R. 32 E., hereinafter described.
40.01	The cor. of secs. 25, 30, 31 and 36, rehabilitated by G. L. Ducret, U.S. Fish and Wildlife Service, in 1950, monumented with a cylindrical concrete monument, 18 ins. long, 3 ins. diam., firmly set showing 2 ins. above ground, with standard brass tablet mkd. 29 R31ER32E SEC25SEC30 SEC36SEC31 T20N 1950.
	This cor. will now refer to secs. 25 and 36 only.
	Remark the brass tablet to read
	29
	R31E R32E
	SEC 25
	SEC 36
	T20N

Set a fiberglass post, 5 ft. long, alongside the stainless steel post.

1950 1992

From this corner, a fence corner bears N. 45° W., 0.05 chs. dist., from which fences bear S. and E.

From this same corner, U.S.G.S. triangulation station and U.S.C.& G.S. Bench Mark monumented with a standard brass tablet mkd. "A 389 1955", cemented flush in 12 in. diam. concrete cylinder showing 8 ins. above ground, bears S. 75°32' E., 33.86 chs. dist.

SURVEY OF THE SOUTH BOUNDARY, T. 20 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

Point for the cor. of Tps. 19 and 20 N., Rs. 32 and 33 E., is at latitude 39°32'47.848" N. and longitude 118°19'49.612" W. (NAD 27), determined 960.00 chs. NORTH of the cor. of Tps. 17 and 18 N., Rs. 32 and 33 E. which is at latitude 39°22'21.812" N. and longitude 118°19'49.612" W. (NAD 27), utilizing GPS Receiver, Ashtech M-XII, monumented with an iron post, 3 ins. diam., firmly set showing 6 ins. above ground, with brass cap mkd. as described in the field notes of T. 17 N., R. 33 E., executed under Group No. 155.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground, over a DEEP-1 magnetic marker, and in a mound of stone, 3 ft. base to top, with brass cap mkd.