

247

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 20 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
7.30	<p>Fence, bears N. 32° W., 2.16 chs. dist. to fence corner, from which fences bear N., W. and S. 32° E., 13.26 chs. dist. to fence corner, from which fences bear N. 32° W. and S. 63³/₄° W.</p>
40.00	<p>Point for the ¹/₄ sec. cor. of secs. 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 24 ins. in the ground, over a DEEP-1 magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T20N R32E ¹/₄ S 10 S 11</p> <p style="text-align: center;">1992</p> <p>Set a fiberglass post, 5 ft. long, alongside the stainless steel post and raise a mound of stone, 2¹/₂ ft. base, 1 ft. high, W. of cor.</p> <p>This corner is located 75 lks. E. of a fence; fence bears irregularly N. and S.</p> <p>From this corner, U.S.G.S. triangulation station and U.S.C. & G.S. Bench Mark monumented with a standard brass tablet mkd. "F 389 1955", cemented flush in 12 in. diam. concrete cylinder showing 4 ins. above ground, bears S. 78°08' E., 5.20 chs. dist.</p>
80.00	<p>Point for the cor. of secs. 2, 3, 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 24 ins. in the ground, over a DEEP-1 magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T20N R32E S 3 S 2 ----- S 10 S 11</p> <p style="text-align: center;">1992</p> <p>Set a fiberglass post, 5 ft. long, alongside the stainless steel post and raise a mound of stone, 2 ft. base, 1 ft. high, W. of cor.</p> <p>This corner is located 22 lks. E. of a fence; fence bears irregularly N. and S.</p> <p>Land, gently rolling. Soil, sandy clay loam. Undergrowth, sagebrush, shadscale and native grass.</p> <hr/> <p>N. 0°01' W., bet. secs. 2 and 3.</p> <p>Over gently rolling land, through scattered undergrowth.</p>
16.00	Fence, bears irregularly N. and S.
40.00	Point for the ¹ / ₄ sec. cor. of secs. 2 and 3.