

256

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 20 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<div style="text-align: center;"> T20N R32E S 29 $\frac{1}{4}$ ——— S 32 </div>
	<div style="text-align: center;">1992</div>
	<p>Set a fiberglass post, 5 ft. long, alongside the stainless steel post.</p> <p>From this corner, U.S.C. & G.S. Bench Mark monumented with a standard brass tablet mkd. "C 389 1955", cemented flush in 12 in. diam. concrete cylinder showing 3 ins. above ground, bears S. 73°22' W., 7.87 chs. dist.</p>
80.00	<p>The cor. of secs. 29, 30, 31 and 32.</p> <p>Land, nearly level. Soil, sandy clay loam. Undergrowth, shadscale and native grass.</p> <hr/>
	<p>WEST, bet. secs. 30 and 31.</p>
	<p>Over nearly level land, through scattered undergrowth.</p>
36.10	<p>Improved bladed road, bears SSE. and NNW.</p>
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 30 and 31, falls on S. edge of improved gravel road.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 12 ins. below the surface of the road, over a DEEP-1 magnetic marker, with brass cap mkd.</p>
	<div style="text-align: center;"> T20N R32E S 30 $\frac{1}{4}$ ——— S 31 </div>
	<div style="text-align: center;">1992</div>
	<p>from which</p> <p>A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 21°00' E., 1.00 chs. dist., with brass cap mkd. RM S30 66.0 FT. 1992 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 69°00' E., 1.00 chs. dist., with brass cap mkd. RM S31 66.0 FT. 1992 and an arrow pointing to the corner.</p>
41.00	<p>Improved gravel road on curve, bears SW. and S. 88½° E.</p>
48.70	<p>Bladed road, bears WSW. and ENE.</p>
81.40	<p>Intersect the E. bdy. of sec. 36, T. 20 N., R. 31 E.</p>