TOWNSHIP 45 NORTH, RANGE 30 EAST, MDM, NEVADA

CHAINS	The vertical angles of measurements made on the slope were ascertained with a theodolite in good adjustment; the horizontal equivalents only are entered in the field notes.
	The geographic position for the southeast corner of the township, is at latitude 41°43'29.4" N. and longitude 118°33'39.0" W. (NAD 27), as calculated along section lines from the previously name triangulation station.
	The mean magnetic declination was found to be 181/2° E.
	DEPENDENT RESURVEY OF THE NINTH STANDARD PARALLEL NORTH, THROUGH A PORTION OF RANGE 30 EAST, MOUNT DIABLO MERIDIAN, NEVADA
	Reestablishment of the Survey Executed by G. W. Garside and C. S. Preble, U. S. Deputy Surveyors, in 1874, and Resurveyed and a Portion Surveyed by W. H. Reppert, U. S. Surveyor, in 1916.
i .	From the standard cor. of Tps. 46 N., Rs. 30 and 31 E., identical with U.S.G.S. triangulation station is at latitude 41°48'45.954" N. and longitude 118°33'52.313" W. (NAD27), monumented with an iron post, 3 ins. diam., firmly set and exposed 10 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey in T. 46 N., R. 30 E., executed under Group No. 42. Add the marks 1991 to the brass cap.
	N. 88°32' W., along the S. bdy. of sec. 36.
	Over rolling land, through scattered sagebrush and native grass.
24.11	The N $^{1}/_{4}$ sec. cor. of sec. 1, T. 45 N., R. 30 E., hereinafter described.
39.80	The standard ¹ / ₄ sec. cor. of sec. 36, monumented with an iron post, 1 in. diam., firmly set and exposed 10 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey in T. 46 N., R. 30 E., executed under Group No. 42. Add the marks T46N R30E 1991 to the brass cap.
	N. 88°31' W., beginning new measurement.
	Over rolling land.
9.30	Fence, parallels highway.
13.20	Nevada State Route 140, on curve from SSE. to N.
16.60	Fence, parallels highway.
23.20	Trail road, bears NNW and SSE.
24.00	The closing cor. of secs. 1 and 2, T. 45 N., R. 30 E., hereinafter described.